

Cabinets for reserved documents MS, class A



Application:

Cabinets assigned for storage of documents that contain non-open information and are marked with “reserved” or “confidential” clause. The most popular cabinets as used in office rooms and archives. Adapted to store important documents, dossiers as well as computer hardware.

Certificates to be stored:

- Class A for storage of “confidential” documents according to the Decree of the Council of Ministers of 1 June 2010.
- Class A for storage of “confidential” documents according to the Decree no. 12/MON of National Defence Minister of 12 March 2010.

Description of the Product:

- Frame and doors made of steel sheet of 1 mm thickness, providing proper rigidity and corrosion protecting;
- Furnished with class A mechanical key lock according to the standard EN 1300 and protected against destruction activity including reborring.
- Cabinet door is blocked with interlocking mechanism on three edges of 12 mm diameter bolts, 112 mm² cross-section and of 450mm maximal spacing (depending on cabinet dimensions)
- Internal shelves are made of steel sheet of 0.8 mm thickness including suspension height adjustment of maximal 50 kg loading.
- Internal hinges
- Door opening angle - 120°
- Guarantee - 24 months

Cabinets for reserved documents MS, class A

Basic equipment:

- Attested key lock of A class with two keys
- Internal shelves
- Product maintenance and usage instruction including guarantee card.

Accessories:

- Hiding boxes of 1mm or 0.8mm thickness metal sheet, closed individually with EuroLocks B671 lock or class A lock according to EN 1300. Hiding boxes in double-door and single-door cabinets are furnished with one chamber and closed with a single key.
- Additional shelves
- Additional key, coded or electronic lock,
- Grip for lead-sealing – pins with cup for lead-sealing imprint
- Two assembling openings in the cabinet bottom
- Fixing anchors

Standard colours:

- Light-grey RAL 7035

Technical data:

Model	Outer dimensions [mm]			Internal dimensions [mm]			Weight [kg]	Capacity [l]
	W	S	G	W	S	G		
Single-door cabinets								
MS1/A 90	900	500	500	825	485	440	34	1,91,
MS1,M/A 90	900	500	400	825	485	340	30	1,48
MS1/A 100	1,000	600	500	925	585	440	39	256
MS1M/A 100	1,000	600	400	925	585	340	35	198
MS1/A 150	1,500	700	500	1,425	685	440	57	451,
MS1M/A 150	1,500	700	400	1,425	685	340	51	348
MS1/A 190	1,900	700	500	1,825	685	440	71	571
MS1S/A 190	1,900	700	460	1,825	685	400	68	51,9
MS1M/A 190	1,900	700	400	1,825	685	340	63	441
Double-door cabinets								
MS2/A 190	1,900	1,000	500	1,825	985	440	93	821,
MS2S/A 190	1,900	1,000	460	1,825	985	400	89	747
MS2M/A 190	1,900	1,000	400	1,825	985	340	84	635

Cabinets for reserved documents MS, class A

Model	Number of shelves	Hiding box*	Box dimensions (WxSxG)
MS1/A 90	2	YES (1)	325x485x405
MS1M/A 90	2	YES (1)	325x485x305
MS1/A 100	2	YES (1 - 2)	325x585x405
MS1M/A 100	2	YES (1 - 2)	325x585x305
MS1/A 150	3	YES (1 - 3)	325x685x405
MS1M/A 150	3	YES (1 - 3)	325x685x305
MS1/A 190	4	YES (1 - 3)	325x685x405
MS1S/A 190	4	YES (1 - 3)	325x685x365
MS1M/A 190	4	YES (1 - 3)	325x685x305
MS2/A 190	4	YES (1 - 3)	325x985x405
MS2S/A 190	4	YES (1 - 3)	325x985x365
MS2M/A 190	4	YES (1 - 3)	325x985x305

*Accessories. Possibility to install even three hiding boxes in one cabinet

Usage:

- Products usage should be in rooms protected against atmospheric factors, situated far from substances of corroding impact to metals. Relative humidity in room – up to 75%. The device may operate in rooms of temperature between +5°C to +40°C.
- When closing or opening the product, attention should be paid to movable elements, e.g.: drawer, door. Improper usage can bring to body injury, such as e.g.: fingers, in the case they are left between drawer and cabinet frame.
- In the time of door closing, attention should be paid to position of bolts; bolts should be strictly hidden; if not, mechanisms could be durably damaged.
- The assembled locks and mechanisms may not be modified under the pain of guarantee loss.
- Only authorised service or a user possessing written service permission may install locks and mechanisms in the time of guarantee period.
- Replacement of the whole lock is recommended in the case keys are needed to be replaced.
- Attention should be paid to the safe setting in a way making impossible for door to strike obstacles directly.
- Locking mechanisms and locks should operate fluently and without jams. In the case there is any objection in relation to operation of subassemblies afore said, such fact should be reported to KONSMETAL service.
- In the case there are any objections in relation to the product delivered they should be reported to KONSMETAL service.
- It is not recommended to make modifications without the manufacturer's knowledge even after the guarantee period completion.

Maintenance:

- **Door:**
It is recommended to lubricate hinges with bearings lubricant if needed, not however rarer that once per three years. All hinges and friction pairs of the mechanisms should be lubricated once per three years with acid-free technical vaseline.
- **Frame:**
In principle, the frame dos not require special preservation treatments. Wetted with mild detergent rag can be used for this purpose and the dried surface can be wiped dry.